

Door Specifications

Door Selection

Style	90-Minute Steel Fire Doors	20-Minute Fire Doors		
	24-Gauge High Definition Steel	Fiberglass Classic-Craft	Fiberglass Fiber-Classic	Fiberglass Smooth-Star
6-Panel	X	X	X	X
4-Panel Square Top	X			X
4-Panel Eyebrow			X	X
3-Panel Scroll Top	X			
3-Panel Craftsman				X
2-Panel Square Top	X			X
2-Panel Soft Arch	X	X		X
2-Panel Soft Arch Plank		X		X
Flush	X		X	X
Flush with vision lite	X			

Field Package Model

Wall Size	Adjusta-Fit® 2 Frame		
	Inswing	Public Access	Corridor
4"-5"	TC403068I	TC403068P	TC403068N
4-1/2"-5-1/2"	TC453068I	TC453068P	TC453068N
5-1/2"-6-1/2"	TC553068I	TC553068P	TC553068N
6-1/2"-7-1/2"	TC653068I	TC653068P	TC653068N
7-1/2"-8-1/2"	TC753068I	TC753068P	TC753068N
8-1/2"-9-1/2"	TC853068I	TC853068P	TC853068N

Note: Example is based on 3'0" x 6'8" nominal size

Nominal Door Size	Common Rough Opening Width	Rough Opening Height Inswing	Rough Opening Height Public Access	Rough Opening Height Corridor
2'0" x 6'8"	25	81-1/4"	80-5/8"	80-1/8"
2'4" x 6'8"	29	81-1/4"	80-5/8"	80-1/8"
2'6" x 6'8"	31	81-1/4"	80-5/8"	80-1/8"
2'8" x 6'8"	33	81-1/4"	80-5/8"	80-1/8"
2'10" x 6'8"	35	81-1/4"	80-5/8"	80-1/8"
3'0" x 6'8"	37	81-1/4"	80-5/8"	80-1/8"
2'0" x 7'0"	25"	85-1/4"	84-5/8"	84-1/8"
2'4" x 7'0"	29"	85-1/4"	84-5/8"	84-1/8"
2'6" x 7'0"	31"	85-1/4"	84-5/8"	84-1/8"
2'8" x 7'0"	33"	85-1/4"	84-5/8"	84-1/8"
2'10" x 7'0"	35"	85-1/4"	84-5/8"	84-1/8"
3'0" x 7'0"	37"	85-1/4"	84-5/8"	84-1/8"

Labeling/Compliance Data

Refer to the Therma-Tru Website for complete specifications and compliance information — www.thermatru.com